

elcometer®
inspection equipment

ENGLAND

Elcometer Limited
Manchester M43 6BU
Tel: +44 (0)161 371 6000
Fax: +44 (0)161 371 6010
e-mail: sales@elcometer.com

FRANCE

Elcometer Sarl
45430 Bou
Tel: +33 (0)2 38 86 33 44
Fax: +33 (0)2 38 91 37 66
e-mail: fr_info@elcometer.com

USA

Elcometer Inc
Rochester Hills Michigan 48309
Tel: +1 248 650 0500
Toll Free: 800 521 0635
Fax: +1 248 650 0501
e-mail: inc@elcometer.com

GERMANY

Elcometer Instruments GmbH
D-73431 Aalen
Tel: +49(0)7361 52806 0
Fax: +49(0)7361 52806 77
e-mail: de_info@elcometer.de

REPUBLIC OF SINGAPORE

Elcometer (Asia) Pte Ltd
Singapore 589472,
Tel: +65 6462 2822
Fax: +65 6462 2860
e-mail: asia@elcometer.com

BELGIUM

Elcometer SA
B-4681 Hermalle /s Argenteau
Tel: +32 (0)4 379 96 10
Fax: +32 (0)4 374 06 03
e-mail: be_info@elcometer.com

JAPAN

Elcometer KK
Nisso Dai 23 Building, Room 804,
3-8-25, Toranomon, Minato-ku,
Tokyo 105-0001
Tel: +81-3-6869-0770
Fax: +81-3-6809-1442
e-mail: jp_info@elcometer.com

THE NETHERLANDS

Elcometer NL
3584 BH Utrecht
Tel: +31 (0)30 210.7005
Fax: +31 (0)30 210.6666
email: nl_info@elcometer.com

Local Distributor: Syntech Surface finishing Specialists
PO Box 19341, 12B Saunders Place, Avondale
Auckland, NEW ZEALAND
Phone: +64 9 820 2121 FAX: +64 9 820 0101
Email: sales@syntechnz.com
www.syntechnz.com

DFT
Fineness of
Grind, Density
Flow & Dip Cups
Rotational Viscosity
Flash Point, Impact Testers
Washability & Abrasion Testers
Film Applicators, Bend Testers, Gloss
Thickness Gauges, Surface Profile, Wet Film
Dry Film, Coating Thickness Gauges
Climatic Testing, Adhesion, Pinhole Testers
Porosity, Software, Dispersion, Inspection Kits
Zahn Cups, Motorised Film Applicators
Drying Time Recorders, Washability, Abrasion
Scratch & Hardness, Elasticity & Deformation
Surface Cleanliness, DOI Gloss Meters
Colour, Moisture, Dewpoint Meters
Cross-Hatch, Oven Recorders
Surface Contamination
ElcoMaster™



Elcometer 138
Bresle Salt Kit

www.elcometer.com

Elcometer 138

Bresle Salt Kit



It is essential that the level of contaminants on a surface is measured prior to application of the coating to ensure the quality of the coating and that its optimum lifetime is achieved.

If the coating is applied to a contaminated surface, which is not properly prepared, it could fail prematurely resulting in costly re-coating and high maintenance costs.

The Elcometer 138 Bresle Kit includes the Elcometer 138 Conductivity Meter. This lightweight, portable conductivity meter accurately measures the salinity of the test samples.

STANDARDS:
 AS 3894.6-A, IMO MSC.215 (82),
 IMO MSC.244 (83), ISO 8502-6,
 ISO 8502-9, SSPC Guide 15,
 US Navy NSI 009-32,
 US Navy PPI 63101-000

The cartridge type sensor can be easily replaced when necessary and displays conductivity in a range of units including: S/cm, S/m, ppm and % salinity.

Technical Specification

Part Number	Description
E138-1	Elcometer 138 Bresle Salt Kit
Measurement Range	0 mS/cm to 19.9 mS/cm and 0 S/m to 1.99 S/m
Accuracy	2% full scale ±1 digit
Dimensions	300 x 220 x 75mm (11 x 8.6 x 3")
Weight	2.1kg (4.62lb)
Packing List	Box of 25 Bresle patches, Elcometer 138 Conductivity Meter, 14ml (0.5fl oz) bottle of standard 1.41 mS/cm calibration solution, 14ml (0.5fl oz) bottle of moistening solution, 250ml (8.5fl oz) bottle of pure water, 3 x 5ml (0.1fl oz) syringes, 3 x blunt needles, 30ml (1fl oz) plastic beaker, 2 x CR2032 lithium batteries, carry case and operating instructions


Accessories

E135----B	Bresle Patches (Box of 25)	T13818519	Plastic Beaker 30ml (1fl oz)
T13818517	3 x 5ml (0.1fl oz) Syringes	T13823926	Calibration Solution 1.41 mS/cm 14ml (0.5fl oz) bottle
T13818518	3 x Needles	T99911344	Pure Water 250ml (8.5fl oz) Bottle


Measuring salt contamination using the Bresle method in accordance with ISO 8502-6/ISO 8502-9




Remove protective backing and foam centre from the patch.
 Apply the patch to surface and press firmly around perimeter to achieve a complete seal - ensuring that a minimum amount of air is trapped within the test compartment.



Insert 3ml of deionised water from the syringe into the patch through its foam perimeter, at a 30° angle, so that it passes through the foam into the test compartment.
 Inject 1.5ml of water into the test compartment.



Reposition the needle and remove the remaining air within the compartment.
 Remove the needle and syringe and hold the syringe with the needle pointing upwards and expel the air.
 Insert the syringe needle into the patch and inject the remaining water.



Withdraw and pull the solution back into the syringe and re-inject back into the patch.
 Repeat at least four times and then extract as much solution as possible.
 Remove the syringe from the patch and measure the conductivity of the solution using a suitable Conductivity Meter such as the Elcometer 138.